



BLUE BLOCK OUT™

2000 Blue

Screen block out tape

Backing

Co-Polymeric Film, Medium Density

PHYSICAL SPECIFICATIONS	
Adhesive	Acrylic
Color	Blue
Film Thickness (mils)	4.0
Tape Thickness (mils)	5.0
*Adhesion to Steel oz./in. width	24-26 oz./inch width
Tensile lb./in.	10
Elongation	150%

**Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

Features

- Solvent & Moisture Resistant
- Remains intact during cleaning cycle
- Conformable in frame corners
- Removes cleanly in one piece without residue
- Aggressive adhesive will not damage screen
- Use on both sides of the screen for maximum protection
- Nationally known as the economical choice for block out tape

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*