



Split Liner Screen block out tape

Backing

Co-Polymeric Film Medium Density

PHYSICAL SPECIFICATIONS	
Adhesive	Acrylic/Rubber
Color	White
Film Thickness (mils)	4.0
Tape Thickness (mils)	5.0
Plastic Release Liner (mils)	4.0
*Adhesion to Steel (oz./in. width)	30 +
Tensile (lb./in.)	10
Elongation	125+ %
Tear Resistance (grams)	50

** Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

Applications

- High Tack Block Out Tape
- Solvent Resistant
- Highly Conformable
- Split Plastic Liner Which Removes Easily Facilitating Application
- Remove One Half Of Liner; Adhesive Half Of The Tape Is Applied To The Screen Mesh; The Other Half Of The Tape(With The Liner Intact) Comes In Contact With The Frame Preventing Adhesive Transfer To The Metal

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*