



4050

STANDARD GRADE SIGN MAKER'S APPLICATION TAPE

BACKING

A standard weight latex saturated paper designed specifically for premask, prespace and application tape requirements.

ADHESIVE

A natural latex adhesive with medium tack levels, which achieves transfer and premasking of mid-sized die cut or prespaced vinyl and printed graphics.

PHYSICAL SPECIFICATIONS	
Adhesive	Natural Latex
Color	White/Translucent
Tape Thickness (PSTC-33)	(100 – 113 microns)
*Adhesion to Steel (PSTC-1)	13 – 15 oz./in. width
Tensile (PSCT-31)	17 lb./in. of width
Elongation	3 – 4%
Tear Resistance (grams)	50

* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

APPLICATIONS

- Application tape for medium sized graphics.
- Premask for printed vinyl graphics.
- Clean transfer with wet application.
- All purpose transfer and prespace tape.

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*

☎ 32-9-216 6709

✉ info@rtape.be ☎ 32-9-216 6700

R Tape Europe:

R Tape
Tech
Data