



4050RLA®

## PREMIUM GRADE PREMASK WITH RELEASE LINER ADHESION TECHNOLOGY

### BACKING

A standard weight latex saturated paper designed specifically for premask, prespace and application tape requirements.

### ADHESIVE

A natural latex adhesive with medium tack levels, which achieves transfer and premasking of mid-sized die cut or prespaced vinyl and printed graphics.

### R TAPE RELEASE LINER ADHESION (RLA™) PERFORMANCE FEATURES

R Tape Premasks upgraded with RLA™ technology have improved adhesion to paper or film release liners, yet maintain the specified adhesion level to the vinyl or printed graphic. R Tape RLA™ Premasks anchor themselves to the release liner for superior lay flat to prevent tunneling and edge curling of stacked or rolled graphics.

Physical Specifications	
Adhesive	Natural rubber
Colour	White / Translucent
Tape Thickness (m, microns)	102 – 115
Adhesion to steel * (N/100mm)	13 – 15
Tensile ( N/25mm)	74
Elongation (%)	3 - 4
Tear Resistance (g)	50

\* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

### APPLICATIONS

- Application tape for medium sized graphics.
- Premask for printed vinyl graphics.
- Clean transfer with wet application.
- All purpose transfer and prespace tape.

**WARRANTY:** R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

32-9-216 6709

info@rtape.be 32-9-216 6700

R Tape Europe:

R Tape Tech Data