



4700

## PREMIUM GRADE PREMASK IDEAL FOR HEAT & VACUUM

### BACKING

A premium grade of heavily saturated paper with higher elongation, resistance to abrasion, moisture and delamination.

### ADHESIVE

A natural rubber adhesive with adhesion levels designed to transfer printed vinyl graphics including clear coated, thermal die cut and heat/vacuum transfers.

PHYSICAL SPECIFICATIONS	
Adhesive	Natural Rubber
Color	White/Translucent
Tape Thickness (mils)	5.0
*Adhesion to Steel (oz./in. width)	9 - 11
Tensile (lb./in.)	19
Elongation	12%
Tear Resistance (grams)	70-80

*\* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

### APPLICATIONS

- Designed for printers, especially those using heat and vacuum processing
- Will not lower high gloss printing due to flat even coating
- Formulated to provide protection and graphic transfer regardless of masked storage time prior to transfer.

**WARRANTY:** *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*

32-9-216 6709

info@rtape.be 32-9-216 6700

R Tape Europe:

R Tape  
Tech  
Data