



4775

PREMIUM GRADE SIGN MAKER'S APPLICATION TAPE

BACKING

A heavyweight saturated paper with higher elongation, resistance to abrasion and moisture, with greater conformability to facilitate placement and transfer of small and large graphics.

ADHESIVE

A natural rubber adhesive with higher tack levels to achieve more consistent transfer of computerized vinyl graphics regardless of size and type. The stable adhesive system permits longer time periods between application of the tape and the actual transfer.

PHYSICAL SPECIFICATIONS	
Adhesive	Natural Rubber
Color	White/Translucent
Tape Thickness (mils)	5.0 – 5.5
*Adhesion to Steel (oz./in. width)	17 – 19
Tensile (lb./in.)	19
Elongation	12%
Tear Resistance (grams)	100

* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

APPLICATIONS

Higher adhesion level combined with the higher tensile, elongation and tear resistant paper provides the sign maker and decal manufacturer with the best possible combination of application tape and pre-space tape.

NOTE: 4775 is not available in factory cut rolls in sizes less than 24".

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*

☎ 32-9-216 6709

✉ info@rtape.be ☎ 32-9-216 6700

R Tape Europe:

R Tape
Tech
Data