



**4776RLA®**

## **PREMIUM GRADE, EXTRA HIGH TACK SIGN MAKER'S APPLICATION TAPE WITH EASY UNWIND & RELEASE LINER ADHESION TECHNOLOGY**

### **BACKING**

A heavyweight saturated paper with higher elongation, resistance to abrasion and moisture, with greater conformability to facilitate placement and transfer of small and large graphics.

### **ADHESIVE**

A natural rubber adhesive with higher tack levels to achieve more consistent transfer of computerized vinyl graphics regardless of size and type. The stable adhesive system permits longer time periods between application of the tape and the actual transfer.

### **R TAPE RELEASE LINER ADHESION (RLA™) PERFORMANCE FEATURES**

R Tape Premasks upgraded with RLA™ technology have improved adhesion to paper or film release liners, yet maintain the specified adhesion level to the vinyl or printed graphic. R Tape RLA™ Premasks anchor themselves to the release liner for superior lay flat to prevent tunneling and edge curling of stacked or rolled graphics.

<b>Physical Specifications</b>	
Adhesive	Natural rubber
Colour	White / Translucent
Tape Thickness (m, microns)	127 – 140
Adhesion to steel * (N/100mm)	20 – 22
Tensile ( N/25mm)	83
Elongation (%)	12
Tear Resistance (g)	100

*\* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

### **APPLICATIONS**

Higher adhesion level combined with the higher tensile, elongation and tear resistant paper provides the sign maker and decal manufacturer with the best possible combination of application tape and pre-space tape.

**WARRANTY:** *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*

R Tape Europe: info@rtape.be ☎ 32-9-216 6700 ☎ 32-9-216 6709

R Tape  
Tech  
Data