



4885

PREMIUM SUPER HIGH TACK PREMASK & APPLICATION TAPE

PAPER

A specially coated, highly saturated heavyweight paper which is designed for moisture resistance and easy unwind.

ADHESIVE

A natural rubber "super-tack" adhesive has been formulated to overcome the broadest range of difficult-to-adhere-to surfaces

PHYSICAL SPECIFICATIONS	
Adhesive	Natural Rubber
Colour	White / Translucent
Tape Thickness	140 – 146 m, microns
Adhesion to Steel*	21 N/100mm
Tensile Strength	70 N/25mm
Elongation (%)	11
Tear Resistance (g)	100

*Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

APPLICATIONS

- Designed for Small Graphics
- Designed for Thermal Die Cut Graphics
- Designed for Highly Textured Surfaces
- Designed for Four-colour UV Clear Coats

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*

☎ 32-9-216 6709

✉ info@rtape.be ☎ 32-9-216 6700

R Tape Europe:

R Tape
Tech
Data