



MATTE FINISH CLEAR APPLICATION FILM

BACKING

Matte finish, polypropylene with excellent clarity, abrasion resistance and lay flat characteristics.

ADHESIVE

An acrylic adhesive designed for clean pick up and transfer performance on all brands of cast or calendered vinyl. The stable adhesive will not build in tack level when applied to vinyl graphics for extended periods of storage, therefore transfer is never a problem.

PHYSICAL SPECIFICATIONS	
Backing	3.7 mil (93μ) matte finish, polypropylene
Adhesive	Acrylic
Color	Transparent
Total Tape Thickness (PSTC-33)	4.3 mil (108 μ)
*Adhesion to Steel (PSTC-1)	7-9
Tensile (PSTC-31)	74-83
Elongation	700%
Application Temperature	Minimum +10°C

•Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

FEATURES

- Forgiving adhesive system! If the adhesive side of the film accidentally folds onto itself, it is easy to pull apart without delamination!
- Exceptional clarity to aid precise registration of multi-color overlays.
- Easy unwind eliminates exhausting application tape struggles.
- Rigid polypropylene facestock minimizes misalignment problems.
- Excellent lay flat to resist curling.
- Unique adhesive system will not build to vinyl during storage of graphics.

WARRANTY: R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.