



CLEAR "EZ-TEAR" APPLICATION FILM

BACKING

An easy-to-tear, embossed transparent polyethylene-based film for transfer of die-cut and computer-cut letters and emblems.

ADHESIVE

A modified acrylic adhesive designed for clean pick up and transfer performance on all brands of cast or calendared vinyl. The stable adhesive will not build in tack level when applied to vinyl graphics for extended periods of storage, therefore transfer is never a problem.

PHYSICAL SPECIFICATIONS	
Film	145mp embossed polyethylene
Adhesive	Modified Polyacrylate
Color	Transparent
Total tape thickness (PSTC-33)	163mp
*Adhesion to steel (PSTC-1)	7-9 N/25mm
Tensile (PSTC-31)	13 Mpa
Elongation	300- 500%
Tear resistance	50-70 grams
Application temperature	Min +10C°

**Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

•FEATURES

- Hand-tearable for easy dispensing
- Forgiving adhesive system! If the adhesive side of the film accidentally folds onto itself, it is easy to pull apart without delamination!
- High tack adhesive system, transfers difficult-to-transfer vinyl graphics and small lettering
- Embossed facestock creates air-egress micro tunnels in the adhesive for bubble-free lamination of the application tape onto the vinyl graphics
- Good clarity to aid precise registration of multi-color overlays.
- Easy unwind eliminates exhausting application tape struggles.
- Rigid polyethylene face stock minimizes misalignment problems.
- Excellent lay flat to resist curling.
- Unique adhesive system will not build to vinyl during storage of graphics.

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*

☎ 32-9-216 6709

✉ info@rtape.be ☎ 32-9-216 6700

R Tape Europe:

R Tape
Tech
Data