

CLEAR SURFACE PROTECTION FILM FOR WIDE FORMAT DIGITAL PRINTS

FACESTOCK

Clear polypropylene with excellent clarity, abrasion resistance and lay flat characteristics.

ADHESIVE

A solventless adhesive designed specifically as a surface protection masking for wide format digital graphics. Adhesion will not build over time and releases easily from the printed graphic upon removal of the surface protection material.

PHYSICAL SPECIFICATIONS	
Backing	83 microns clear polypropylene
Adhesive	Solventless
Color	Transparent
Total Tape Thickness (mils)	4.5 (115 microns)
*Adhesion to Steel (oz./in. width)	4 – 7 (4.3 – 7.7 N/100mm)
Tensile (lb./in.)	17 – 19 (297-332 N/100mm)
Elongation	100% +

**Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

FEATURES

- Excellent clear surface protection film for wide format digital solvent based printed prints!
- Very good clarity to allow inspection of printed graphics.
- Rigid polypropylene facestock resists stretching to prevent graphics misalignment during application.
- Unwinds easily for more user-friendly lamination.
- Removes easily without pulling overlaminates from the graphics or applied graphics from the substrate.

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*