



PM42

CLEAR EZ TEAR PREMASK

R Tape PM-42 Clear EZ Tear Premask is a matte finished co-polymeric clear plastic film with a medium level adhesive system for premasking printed and unprinted vinyl and polycarbonate sign graphics. Designed for immediate or long-term applications.

PHYSICAL SPECIFICATIONS	
Adhesive	Natural Rubber
Color	Transparent
Total Tape Thickness (mils)	5.5 - 6 Mils
*Adhesion to Steel (oz./in. width)	7 - 8
Tensile (lb./in.)	10
Elongation	150%
Tear Resistance (grams)	50

•Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

APPLICATIONS:

- Tears easily by hand to facilitate dispensing.
- Improved handling characteristics makes premask laminations easier and wrinkle-free.
- No adhesion build up to graphics allows for easy removal, even after prolonged storage .
- Upon removal, adhesive does not delaminate. No adhesive mess eliminates time-consuming clean up.
- An excellent premask for protecting printed vinyl graphics or polycarbonate signage.
- Works well in “wet applications”.

WARRANTY: *R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored @ 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.*

☎ 32-9-216 6709

✉ info@rtape.be ☎ 32-9-216 6700

R Tape Europe:

R Tape
Tech
Data